



TUV SUD America Inc.
Product Safety Services
 1755 Atlantic Blvd.
 Auburn Hills, MI 48326
 Phone: (616) 546-4600

Surfacing Material Report - Least Favorable Impact Location – ASTM F1292-18

Client:	Project No.:
Manufacturer:	Report Date:
Manufacturing Location:	Test Date:
	Initial Test:
Phone:	Follow up Test: Ref Job:
Commercial Name of Product:	Sample Receipt Date:
Date of Manufacture:	Ambient Air Temperature: °C
No. of samples submitted:	Humidity: %

Test Equipment:

Alpha Automation, Triax, TUV System 5:	Environmental Chamber No.:
Alpha Automation, Triax, TUV System 7:	Calibration Due Date:
Accelerometer ID:	Environmental Chamber No.:
Accelerometer Calibration Date:	Calibration Due Date:

Sample Layer Description:

Tiles:	Total System Thickness: _____
Turf:	Top Layer: _____
Other:	Base Layer: _____

Determine Least Favorable Impact Location: The highest percentage (%), of maximum allowable value, based on g-max or HIC, as tested at the locations indicated on Pages 2 and 3.

	<u>Impact Location:</u>	<u>Reference Temperature:</u>
Least Favorable Impact Location was determined at:	_____	23°C

Comments:

- 1.) Samples tested in laboratory environment, overlying poured concrete floor.
- 2.) Calculate the average g-max and HIC scores by averaging results from the second and third impacts.
- 3.) After Least Favorable Impact Location is determined at 23°C, remaining testing will be completed at temperatures 49°C and -6°C at that location.

The above described sample was tested at : Ft.

The results reported herein reflect the performance of the above described samples at the time of testing and at the temperature(s) reported. The results are specific to the described samples. Samples of surfacing materials that do not closely match the described samples will perform differently. The following data sheet provides an accurate representation of the test results. Compliance with this Standard does not constitute product certification.

Sample in compliance with ASTM F1292-18 at the temperature and rating specified? Yes No

Signature: *RDP* Title: _____ Date: _____

Reviewed by: *Timothy Foubia* Title: _____ Date: _____

Client:

Project No.:

Manufacturer:

Test Date:

Impact Location:

Drop	Specified Impact Height (Ft.)	Reference Temperature -6°C, (21.2°F)				Reference Temperature 23°C, (73.4°F)				Reference Temperature 49°C, (120.2°F)					
		G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)		
1															
2															
3															
Average															
Measured Surface Temperature	°C	Max. Change from reference + 5°C, (5°F)				23°C	Max. Change from reference ± 3°C, (±5°F)				°C	Max. Change from reference -3°C, (-5°F)			
Sample Condition:	DRY				DRY				DRY						
Percentage (%) of maximum allowable values (g-max and HIC):					G-Max:		HIC:								

Impact Location:

Drop	Specified Impact Height (Ft.)	Reference Temperature -6°C, (21.2°F)				Reference Temperature 23°C, (73.4°F)				Reference Temperature 49°C, (120.2°F)					
		G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)		
1															
2															
3															
Average															
Measured Surface Temperature	°C	Max. Change from reference + 5°C, (5°F)				23°C	Max. Change from reference ± 3°C, (±5°F)				°C	Max. Change from reference -3°C, (-5°F)			
Sample Condition:	DRY				DRY				DRY						
Percentage (%) of maximum allowable values (g-max and HIC):					G-Max:		HIC:								

Impact Location:

Drop	Specified Impact Height (Ft.)	Reference Temperature -6°C, (21.2°F)				Reference Temperature 23°C, (73.4°F)				Reference Temperature 49°C, (120.2°F)					
		G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)		
1															
2															
3															
Average															
Measured Surface Temperature	°C	Max. Change from reference + 5°C, (5°F)				23°C	Max. Change from reference ± 3°C, (±5°F)				°C	Max. Change from reference -3°C, (-5°F)			
Sample Condition:	DRY				DRY				DRY						
Percentage (%) of maximum allowable values (g-max and HIC):					G-Max:		HIC:								



America

Client:

Project No.:

Manufacturer:

Test Date:

Impact Location:

Drop	Specified Impact Height (Ft.)	Reference Temperature -6°C, (21.2°F)				Reference Temperature 23°C, (73.4°F)				Reference Temperature 49°C, (120.2°F)			
		G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)
1													
2													
3													
Average													
Measured Surface Temperature		°C	Max. Change from reference + 5°C, (5°F)			23°C	Max. Change from reference ± 3°C, (±5°F)			°C	Max. Change from reference -3°C, (-5°F)		
Sample Condition:		DRY				DRY				DRY			
Percentage (%) of maximum allowable values (g-max and HIC):						G-Max:		HIC:					

Impact Location:

Drop	Specified Impact Height (Ft.)	Reference Temperature -6°C, (21.2°F)				Reference Temperature 23°C, (73.4°F)				Reference Temperature 49°C, (120.2°F)			
		G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)
1													
2													
3													
Average													
Measured Surface Temperature		°C	Max. Change from reference + 5°C, (5°F)			23°C	Max. Change from reference ± 3°C, (±5°F)			°C	Max. Change from reference -3°C, (-5°F)		
Sample Condition:		DRY				DRY				DRY			
Percentage (%) of maximum allowable values (g-max and HIC):						G-Max:		HIC:					

Impact Location:

Drop	Specified Impact Height (Ft.)	Reference Temperature -6°C, (21.2°F)				Reference Temperature 23°C, (73.4°F)				Reference Temperature 49°C, (120.2°F)			
		G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)	G-Max	HIC	Velocity (ft/s)	Theoretical Drop Height (ft.)
1													
2													
3													
Average													
Measured Surface Temperature		°C	Max. Change from reference + 5°C, (5°F)			23°C	Max. Change from reference ± 3°C, (±5°F)			°C	Max. Change from reference -3°C, (-5°F)		
Sample Condition:		DRY				DRY				DRY			
Percentage (%) of maximum allowable values (g-max and HIC):						G-Max:		HIC:					



America