

Technical Data Sheet: PlayFall[®]



When kids play, they also fall, and that's where PlayFall® comes to the rescue. PlayFall® is designed to meet stringent ASTM requirements for playground fall protection and is available in a variety of thicknesses to match the fall heights of most play equipment and events.

Don't play on anything less!



10 YEAR WARRANTY Including impact attenuation to Fizgz

PlayFall[®] Tile Details


- Tiles are 2' x 2' and feature a 1' x 1' cross-hatch surface pattern
- Available in 1.75" and 3.15" thicknesses with PlayPad underlayments
- Slip resistant
- Minimal maintenance
- Porous for effective drainage
- Quick interlocking installation with plastic pins and minimal adhesive
- Made from 100% recycled SBR truck tire rubber buffings and granules in a non-toxic polyurethane binder

PlayPad Details

- Pads are 4' x 5'
- Thickness options: 1" or 2"
- PlayPad products are made from 100% recycled materials
- 100% nonwoven Geotextile
- Non-toxic and environmentally friendly
- Superior drainage rate
- Long lifespan and stability
- Impact protection and energy absorption

Drop Height Configurations - Tested to ASTM F1292-18 Impact Attenuation Requirements -

Fall Height	Configuration Required
4'	1.75" PlayFall® Tile
6'	3.15" PlayFall® Tile
8'	1.75" PlayFall® Tile + 2.0" PlayPad
10'	1.75" PlayFall® Tile + 1.0" PlayPad + 2.0" PlayPad





Black

Green

Terra Cotta