

ProXL Technical Data

Hardness Shore A

Compression Set Coefficient of Friction

Tensile Strength

Static Load Limit

Tear Strength

Elongation at Break

Moisture Absorption

Critical Radiant Flux

Optical Density of Smoke

Resistance to Chemicals

Wear Layer Thickness

Abrasion Resistance

Dimensional Stability VOC Compliance

Thickness

Squareness

Quality of Cut

Color Stability

Light Reflection

Contributes to LEED Points

Construction:

Wear Surface:

Base Layer:

Rolls

Tiles

Anti-microbial/Anti-fungal Properties

Thickness

3.5mm

6mm

8mm

10mm 3.5mm

6mm

8mm

10mm

512

560

Size

Resistance to Heat

Static Coefficient of Friction

Technical Specifications

ASTM D2240

ASTM D395

ASTM D2047

ASTM C-1028

ASTM D412

ASTM D412

ASTM D624

ASTM F970-00

ASTM D570

ASTM E648-03, NFPA253

ASTM F-1514

ASTM E662

ASTM F-925

ASTM F-410

ASTM D-3389

ASTM F-2199

CA 01350

ASTM F386

ASTM F2055

ASTM F2055

ASTM F511

Size Specifications

Dimension

4' x 50'

(±1.22m x 15.24m)

4' x 30'

(±1.22m x 9.15m)

1m x 1m

Standard Colors

10mm interlock 0.945 m x 0.945 m

Dual-layer Vulcanized Rubber

Weight

0.90 lb./sq.ft.

1.8 lb./sq.ft.

2.4 lb./sq.ft.

3.2 lb./sq.ft.

16 lbs.

23 lbs.

30 lbs.

38 lbs.

31 lbs.

530

575

Color Virgin Blend Rubber 55% Recycled Rubber



80 ± 5

0.0993

dry > 0.8

> 1.0 Wet / Dry

Top >300% / Bot >200%

>25kN/m

Passes

0.0037

Class I > 0.45 watts/cm²

Passes

Class 1 < 450

Passes

Passes

Passes

Passes

Yes

Passes

Passes

Passes

Passes

Good

Average

Yes

Yes

Area

200 sq.ft. or 18.59 sq.m

120 sq.ft. or 11.16 sq.m

10.75 sq. ft.

9.6 sq.ft.

541

Top >1000psi / Bot >350psi



ProXL

Solid color with marble accent, dual layer, rubber flooring. ProXL's slip-resistant, textured top wear layer provides a non-porous, safe and resilient floor finish. ProXL is a great fit for weight rooms, ice rinks, fitness centers or home gyms.





Special Order: Top Wear Layer 3mm Custom logo

Finishes: Matte only

Colors:

oniy				1				
Fossil [5	12] Smoke [515]	Graphite [530]	Indigo [5/1]	Chocolate [560]	Maple [568]	Elm [575]	Eiro [585]	

Fossil [512], Smoke [515], Graphite [530], Indigo [541], Chocolate [560], Maple [568], Elm [575], Fire [585]

Colors shown are only indicative, as true color reproduction is not possible Colors will be matched to within \pm one tone on the pantone chart

North West Rubber Ltd. 33850 Industrial Avenue Abbotsford, BC Canada V2S 7T9 T 604.859.2002 F 604.859.2009 TF 1.800.663.8724