

Stamina

100% recycled vulcanized flooring that can be adhered, loose laid, or interlocked. The non-porous surface makes it an ideal flooring product for use in hockey arenas, free weight and fitness facilities or anywhere that a tough, slip-resistant, easy-to-clean floor is required.



Special Order:

Custom logo cutting available









Finishes:

Smooth top

Technical Specifications		
Hardness Shore A	ASTM D2240	75+/-5
Wear Layer Thickness	ASTM F410	Passes
Static Load Resistance	ASTM F970	Passes
Resistance to Chemicals	ASTM F925	Good
Resistance to Heat	ASTM F1514	Passes
Abrasion Resistance	ASTM D3389	< 0.5 grams loss
Dimensional Stability	ASTM F2199	Passes
Critical Radiant Flux	ASTM E648-03	Class II
Co-efficient of Friction	ASTM C1028	>.80 dry >.64 wet
Moisture Absorption	ASTM D570	0.27%
Thickness	ASTM F386	Passes
Size	ASTM F2055	Passes
Squareness	ASTM F2055	Passes
Quality of Cut	ASTM F511	Passes
Qualifies for LEED Points		Yes
Anti-microbial/Anti-fungal Properties		Yes

Size Specifications						
Construction - 100% recycled vulcanized rubber						
Thickness	Square			Interlock		
	Dimension	Weight	Area	Dimension	Weight	Area
8mm (5/16")	48" x 72"	48 lbs.	24 sq.ft.	22.2" x 22.2"	7 lbs.	3.42 sq.ft.
10mm (3/8")	48" x 72"	60 lbs.	24 sq.ft.	44.3" x 66.5"	56 lbs.	20.46 sq. ft.
				22.2" x 22.2"	9 lbs.	3.42 sq. ft.
12mm (1/2")	48" x 72"	70 lbs.	24 sq.ft.	44.3" x 66.5"	66 lbs.	20.46 sq. ft.
17mm* (3/4")	48" x 72"	100 lbs.	24 sq.ft.	44.3" x 66.5"	86 lbs.	20.46 sq. ft.

* black only

Standard Colors			
			
			

Colors: Black [100], Red Speckle [110], Grey Speckle[120], Blue Speckle [130], Green Speckle [150], Orange Speckle [160], Yellow Speckle [170], Earth Speckle[190]

Custom colors are available by special order

Colors shown are only indicative, as true color reproduction is not possible