

# ENDEAVOR TECHNICAL DATA SHEET

## PRODUCT DESCRIPTION

North West Rubber's Endeavor mats are constructed with 10mm (3/8") thick, 100% recycled vulcanized rubber. Endeavor's smooth and uniform surface finish, vulcanized durability, ease of install and budget-friendly price make them the superior choice for fitness and weight room applications versus comparably priced 8mm (5/16") polyurethane mats or stall mat alternatives.

## TECHNICAL SPECIFICATIONS

Hardness Shore A	ASTM D2240	70 +/- 5
Wear Layer Thickness	ASTM F410	0.387 (Passes)
Static Load Resistance	ASTM F970	0.001 (Passes)
Resistance to Chemicals	ASTM F925	Good
Resistance to Heat	ASTM F1514	1.71 (Passes)
Abrasion Resistance	ASTM D3389	0.14 gr. (Passes)
Dimensional Stability	ASTM F2199	0.15 (Passes)
Smoke Density (Flaming Mode)	ASTM E662	420 DC (Passes)
Thickness	ASTM F386	(Passes)
Size	ASTM F2055	Avg. 0.015 (Passes)
Squareness	ASTM F2055	Avg. 0.004 (Passes)
Quality of Cut	ASTM F511	Avg. 0.001 (Passes)
Qualifies for LEED® Points	-	Yes
Anti-microbial / Anti-fungal properties	-	Yes


## SPECS

Construction: 100% recycled rubber.



THICKNESS	DIMENSIONS	WEIGHT	AREA
<b>STRAIGHT-EDGED MATS</b>			
3/8" (10mm)	4' x 6' (1.22m x 1.83m)	58 lbs./mat (26.3kg)	24 sq.ft. (7.32 sq.m.)
<b>INTERLOCKING MATS &amp; TILES</b>			
3/8" (10mm)	3.69' x 5.54' (1.13m x 1.69m)	54 lbs./mat (24.5kg)	20.46 sq.ft. (6.24 sq.m.)

## STANDARD COLOR



Black

## FEATURES & BENEFITS

- Vulcanized Durability**
- 99.5% Anti-Microbial**
- 100% Recycled Rubber**
- Made in Canada**

